

Compare Products

Code	71382
Model	XK



Note	<p>ERON D-1 DASHBOARD Connect Calypso Connect (Motor, Battery, ERON D-1) Dual Speed trigger Fiber Carbon Proplock Propeller Battery Gauge Bypass System HD Shaft Seal Carry Handle Cleaning and Lubrication Kit Tow Leash with boltsnap and bungee Extra Bolt snap</p> <p>- Top speed is delivered with fully charged battery - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim - Conditions : sea water - no flow/current</p>
-------------	---

Dimensions

Use	TECH / COMMERCIALLONG RANGE / CAVE
Length	mm 975 (inch 38,4)
Width	mm 462 (inch 18,2)
Height	mm 364 (inch 14,33)
Body diameter	mm 197 (inch 7,8)
Weight without battery	kg 17 (lb 37,48)
Weight with battery	kg 25 (lb 55,12)
Material type	Aluminum Body

Performance

Max static thrust	N 375 (lb 84,3)
Top speed	mt/min 100 (ft/min 328)
Run time at max speed/drag	min 100
Run time at cruise speed	min 330
Maximum operational depth	mt 200 (ft 656)
Test depth	mt 300 (ft 984)
Buoyancy/ trim	Neutral Trim and Buoyancy

In-water usage temperature °C -5/+35 (°F +23/+95)

Runtime-range	SPEED	BURNTIME	RANGE
	FULL TRIGGER	100 MIN	8,1 (4,3) KM (nm)
	80 MT/MIN	120 MIN	9,6 (4,9) KM (nm)
	60 MT/MIN	200 MIN	12,0(7,0) KM (nm)
	CRUISE 45 MT/MIN	330 MIN	14,8(7,5) KM (nm)

- Top speed is delivered with fully charged battery
 - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim
 - Conditions : sea water - no flow/current

Battery type

Battery type	LI-ion
Nominal Voltage	Volt 36
Nominal Capacity	Wh 1340
Maximum recharging time	h 8
Charger power supply	90/240 - 50/60 Hz

Features

Smartphone connect	●
External Charge	
Battery Gauge	●
Li-ion Battery	●
Fastening device	●
Main Switch	●
Proplock Propeller	●
Speed Adjustment	●
By-pass System	●
Easy Trim	●
Easy Inspect	●
New Handle Design	●
Sealed Motor Compartment	●
NBS - Neutral Buoyancy System	●
Made Salt Resistant	●
Motor Protection	●
Battery Protection	●
Certifications	●

Features legend:

● : standard

○ : optional

 : not available